



聯絡電話: 02-8911-2728

Email: sales@globalsil.com.tw

- [1] J. Li *et al.*, “Enhancing the efficiency and longevity of inverted perovskite solar cells with antimony-doped tin oxides,” *Nat Energy*, vol. 9, no. 3, pp. 308–315, Mar. 2024, doi: [10.1038/s41560-023-01442-1](https://doi.org/10.1038/s41560-023-01442-1).
- [2] X. Tang *u. a.*, „Enhancing the efficiency and stability of perovskite solar cells via a polymer heterointerface bridge“, *Nat. Photon.*, Juni 2025, doi: [10.1038/s41566-025-01676-3](https://doi.org/10.1038/s41566-025-01676-3).
- [3] R. Guo *et al.*, “Refining the Substrate Surface Morphology for Achieving Efficient Inverted Perovskite Solar Cells,” *Advanced Energy Materials*, vol. 13, no. 43, p. 2302280, 2023, doi: [10.1002/aenm.202302280](https://doi.org/10.1002/aenm.202302280).
- [4] O. Er-raji *et al.*, “Tailoring perovskite crystallization and interfacial passivation in efficient, fully textured perovskite silicon tandem solar cells,” *Joule*, vol. 0, no. 0, Jul. 2024, doi: [10.1016/j.joule.2024.06.018](https://doi.org/10.1016/j.joule.2024.06.018).
- [5] Q. Ning *et al.*, “Homogenizing Electron and Hole Transport Layers in Tin Perovskite Solar Cells to Enhance Photocurrent and Voltage,” *ACS Appl. Mater. Interfaces*, May 2025, doi: [10.1021/acsami.5c05263](https://doi.org/10.1021/acsami.5c05263).
- [6] A. Callies *et al.*, “Optical Reabsorption Effects in Photoluminescence of Perovskites Conformally Coated on Textured Silicon,” *Solar RRL*, vol. n/a, no. n/a, p. 202500048, doi: [10.1002/solr.202500048](https://doi.org/10.1002/solr.202500048).
- [7] T. Burgard *et al.*, “Transformation of Lead Iodide (Cs_{0.05}PbI_{2.05}) during Annealing and Its Influence on Perovskite Formation and Solar Cells,” *Solar RRL*, vol. n/a, no. n/a, p. 202400746, doi: [10.1002/solr.202400746](https://doi.org/10.1002/solr.202400746).
- [8] J. K. Pious *et al.*, “Efficient Blade-Coated Wide-Bandgap Perovskite Solar Cells via Interface Engineering,” *ACS Appl. Mater. Interfaces*, vol. 17, no. 16, pp. 24040–24047, Apr. 2025, doi: [10.1021/acsami.5c03709](https://doi.org/10.1021/acsami.5c03709).
- [9] Y. Yuan, G. Yan, S. Akel, U. Rau, and T. Kirchartz, “Deriving mobility-lifetime products in halide perovskite films from spectrally- and time-resolved photoluminescence,” Nov. 04, 2024, *arXiv*: arXiv:2411.01912. doi: [10.48550/arXiv.2411.01912](https://doi.org/10.48550/arXiv.2411.01912).

- [10] A. Al-Ashouri *et al.*, “Wettability Improvement of a Carbazole-Based Hole-Selective Monolayer for Reproducible Perovskite Solar Cells,” *ACS Energy Lett.*, vol. 8, no. 2, pp. 898–900, Feb. 2023, doi: [10.1021/acsenergylett.2c02629](https://doi.org/10.1021/acsenergylett.2c02629).
- [11] D. O. Baumann, F. Laufer, J. Roger, R. Singh, M. Gholipour, and U. W. Paetzold, “Repeatable Perovskite Solar Cells through Fully Automated Spin-Coating and Quenching,” *ACS Appl. Mater. Interfaces*, vol. 16, no. 40, pp. 54007–54016, Oct. 2024, doi: [10.1021/acsami.4c13024](https://doi.org/10.1021/acsami.4c13024).
- [12] K. Nguyen *et al.*, “The Role of Luminescent Coupling in Monolithic Perovskite/Silicon Tandem Solar Cells,” *Small*, vol. n/a, no. n/a, p. 2403461, doi: [10.1002/sml.202403461](https://doi.org/10.1002/sml.202403461).
- [13] H. Liang *et al.*, “29.9%-efficient, commercially viable perovskite/CuInSe₂ thin-film tandem solar cells,” *Joule*, vol. 7, no. 12, pp. 2859–2872, Dec. 2023, doi: [10.1016/j.joule.2023.10.007](https://doi.org/10.1016/j.joule.2023.10.007).
- [14] M. Heydarian *et al.*, “Maximizing Current Density in Monolithic Perovskite Silicon Tandem Solar Cells,” *Solar RRL*, vol. 7, no. 7, p. 2200930, 2023, doi: [10.1002/solr.202200930](https://doi.org/10.1002/solr.202200930).
- [15] O. Er-raji *et al.*, “Loss Analysis of Fully-Textured Perovskite Silicon Tandem Solar Cells: Characterization Methods and Simulation toward the Practical Efficiency Potential,” *Solar RRL*, vol. 7, no. 24, p. 2300659, 2023, doi: [10.1002/solr.202300659](https://doi.org/10.1002/solr.202300659).
- [16] O. Er-raji *et al.*, “Toward efficient and industrially compatible fully textured perovskite silicon tandem solar cells: Controlled process parameters for reliable perovskite formation,” *Progress in Photovoltaics: Research and Applications*, vol. n/a, no. n/a, doi: [10.1002/pip.3770](https://doi.org/10.1002/pip.3770).
- [17] R. Pappenberger, A. Diercks, J. Petry, S. Moghadamzadeh, P. Fassl, and U. W. Paetzold, “Bandgap Engineering of Two-Step Processed Perovskite Top Cells for Perovskite-Based Tandem Photovoltaics,” *Advanced Functional Materials*, vol. 34, no. 9, p. 2311424, 2024, doi: [10.1002/adfm.202311424](https://doi.org/10.1002/adfm.202311424).
- [18] O. Er-raji, L. Rustam, B. P. Kore, S. W. Glunz, and P. S. C. Schulze, “Insights into Perovskite Film Formation Using the Hybrid Evaporation/Spin-Coating Route: An In Situ XRD Study,” *ACS Appl. Energy Mater.*, vol. 6, no. 11, pp. 6183–6193, Jun. 2023, doi: [10.1021/acsaem.3c00698](https://doi.org/10.1021/acsaem.3c00698).
- [19] O. Fischer *et al.*, “Versatile implied open-circuit voltage imaging method and its application in monolithic tandem solar cells,” *Progress in Photovoltaics: Research and Applications*, vol. n/a, no. n/a, doi: [10.1002/pip.3754](https://doi.org/10.1002/pip.3754).



聯絡電話：02-8911-2728

Email: sales@globalsilicon.com.tw